

TELO INDUSTRIES

www.telindustries.com

| | |
|------|--|
| ITEM | PP Gloss White Cavitated -Hotmelt /60 g Yellow Glassine Liner |
|------|--|

| FACE STOCK | | LINER | |
|---------------|----------------|-------------|-----------------|
| PRODUCT NAME | PP Gloss White | NAME | Yellow Glassine |
| THICKNESS | 60um | THICKNESS | 52um |
| GSM | 44 gsm +/- 2 | GSM | 60gsm |
| COLOUR | Gloss White | COLOUR | YELLOW |
| SMOOTHNESS | GOOD | SMOOTHNESS | GOOD |
| PRINT ABILITY | GOOD | DIE CUTTING | GOOD |

| PRESSURE SENSITIVE ADHESIVE | | | | |
|-----------------------------|---------|------------------|-----|------|
| ADHESIVE TYPE | Hotmelt | GSM OF GLUE | 18g | |
| THICKNESS | 18um | LOOP TACK | 25 | |
| HOLD TACK | 72h | 90°PEEL ADHESION | 16 | |
| MIN LABELING TEMP °C | 5°C | SERVICE TEMP °C | -20 | 65°C |

Storage And Shelf Life

The standard Shelf life in this material is 12 to 24 months, this product must be stored at 20 to 24 degrees Celsius with minimal humidity, this product must be kept in its original packaging when not in use, in order for it be free from dust .this product must not be exposed to any elements such as , rain ,sunlight or cold/hot temperatures.

Safety

All users must take note and understand the safety data sheet and follow all general workplace safety procedures to ensure no loss or damage.

Telo Industries can assure you that all data presented is believed to be true and accurate as per our internal testing and evaluation, however this is no guarantee, please allow for a 10% variation either way